

(3) Provide a sampling port for monitoring within the exhaust outlet of the carbon adsorber that is easily accessible and located at least 8 stack or duct diameters downstream from any flow disturbance such as a bend, expansion, contraction, or outlet; downstream from no other inlet; and 2 stack or duct diameters upstream from any flow disturbance such as a bend, expansion, contraction, inlet, or outlet.

(c) If the air-perchloroethylene gas-vapor stream is passed through a carbon adsorber prior to machine door opening to comply with § 63.322(b)(3), the owner or operator of an affected facility shall measure the concentration of perchloroethylene in the dry cleaning machine drum at the end of the dry cleaning cycle weekly with a colorimetric detector tube to determine that the perchloroethylene concentration is equal to or less than 300 parts per million by volume. The owner or operator shall:

(1) Use a colorimetric detector tube designed to measure a concentration of 300 parts per million by volume of perchloroethylene in air to an accuracy of ± 75 parts per million by volume; and

(2) Use the colorimetric detector tube according to the manufacturer's instructions; and

(3) Conduct the weekly monitoring by inserting the colorimetric detector tube into the open space above the articles at the rear of the dry cleaning machine drum immediately upon opening the dry cleaning machine door.

(d) When calculating yearly perchloroethylene consumption for the purpose of demonstrating applicability according to § 63.320, the owner or operator shall perform the following calculation on the first day of every month:

(1) Sum the volume of all perchloroethylene purchases made in each of the previous 12 months, as recorded in the log described in § 63.324(d)(1).

(2) If no perchloroethylene purchases were made in a given month, then the perchloroethylene consumption for that month is zero gallons.

(3) The total sum calculated in paragraph (d) of this section is the yearly perchloroethylene consumption at the facility.

§ 63.324 Reporting and recordkeeping requirements.

(a) Each owner or operator of a dry cleaning facility shall notify the Administrator or delegated State authority in writing within 270 calendar days after September 23, 1993 (i.e., June 18, 1994) and provide the following information:

(1) The name and address of the owner or operator;

(2) The address (that is, physical location) of the dry cleaning facility;

(3) A brief description of the type of each dry cleaning machine at the dry cleaning facility;

(4) Documentation as described in § 63.323(d) of the yearly perchloroethylene consumption at the dry cleaning facility for the previous year to demonstrate applicability according to § 63.320; or an estimation of perchloroethylene consumption for the previous year to estimate applicability with § 63.320; and

(5) A description of the type of control device(s) that will be used to achieve compliance with § 63.322 (a) or (b) and whether the control device(s) is currently in use or will be purchased.

(6) Documentation to demonstrate to the Administrator's satisfaction that each room enclosure used to meet the requirements of § 63.322(a)(3) meets the requirements of § 63.322(a)(3) (i) and (ii).

(b) Each owner or operator of a dry cleaning facility shall submit to the Administrator or delegated State authority by registered mail on or before the 30th day following the compliance dates specified in § 63.320 (b) or (c) or June 18, 1994, whichever is later, a notification of compliance status providing the following information and signed by a responsible official who shall certify its accuracy:

(1) The yearly perchloroethylene solvent consumption limit based upon the yearly solvent consumption calculated according to § 63.323(d);

(2) Whether or not they are in compliance with each applicable requirement of § 63.322; and

(3) All information contained in the statement is accurate and true.

(c) Each owner or operator of an area source dry cleaning facility that exceeds the solvent consumption limit

§ 63.325

40 CFR Ch. I (7–1–00 Edition)

reported in paragraph (b) of this section shall submit to the Administrator or a delegated State authority by registered mail on or before the dates specified in § 63.320 (f) or (i), a notification of compliance status providing the following information and signed by a responsible official who shall certify its accuracy:

(1) The new yearly perchloroethylene solvent consumption limit based upon the yearly solvent consumption calculated according to § 63.323(d);

(2) Whether or not they are in compliance with each applicable requirement of § 63.322; and

(3) All information contained in the statement is accurate and true.

(d) Each owner or operator of a dry cleaning facility shall keep receipts of perchloroethylene purchases and a log of the following information and maintain such information on site and show it upon request for a period of 5 years:

(1) The volume of perchloroethylene purchased each month by the dry cleaning facility as recorded from perchloroethylene purchases; if no perchloroethylene is purchased during a given month then the owner or operator would enter zero gallons into the log;

(2) The calculation and result of the yearly perchloroethylene consumption determined on the first day of each month as specified in § 63.323(d);

(3) The dates when the dry cleaning system components are inspected for perceptible leaks, as specified in § 63.322(k) or (l), and the name or location of dry cleaning system components where perceptible leaks are detected;

(4) The dates of repair and records of written or verbal orders for repair parts to demonstrate compliance with § 63.322(m) and (n);

(5) The date and temperature sensor monitoring results, as specified in § 63.323 if a refrigerated condenser is used to comply with § 63.322(a) or (b); and

(6) The date and colorimetric detector tube monitoring results, as specified in § 63.323, if a carbon adsorber is used to comply with § 63.322(a)(2) or (b)(3).

(e) Each owner or operator of a dry cleaning facility shall retain onsite a

copy of the design specifications and the operating manuals for each dry cleaning system and each emission control device located at the dry cleaning facility.

[58 FR 49376, Sept. 22, 1993, as amended at 58 FR 66289, Dec. 20, 1993]

§ 63.325 Determination of equivalent emission control technology.

(a) Any person requesting that the use of certain equipment or procedures be considered equivalent to the requirements under § 63.322 shall collect, verify, and submit to the Administrator the following information to show that the alternative achieves equivalent emission reductions:

(1) Diagrams, as appropriate, illustrating the emission control technology, its operation and integration into or function with dry-to-dry machine(s) or transfer machine system(s) and their ancillary equipment during each portion of the normal dry cleaning cycle;

(2) Information quantifying vented perchloroethylene emissions from the dry-to-dry machine(s) or transfer machine system(s) during each portion of the dry cleaning cycle with and without the use of the candidate emission control technology;

(3) Information on solvent mileage achieved with and without the candidate emission control technology. Solvent mileage is the average weight of articles cleaned per volume of perchloroethylene used. Solvent mileage data must be of continuous duration for at least 1 year under the conditions of a typical dry cleaning operation. This information on solvent mileage must be accompanied by information on the design, configuration, operation, and maintenance of the specific dry cleaning system from which the solvent mileage information was obtained;

(4) Identification of maintenance requirements and parameters to monitor to ensure proper operation and maintenance of the candidate emission control technology;

(5) Explanation of why this information is considered accurate and representative of both the short-term and the long-term performance of the candidate emission control technology on